


# Product data sheet

NADJA II/1 LED (1 BRACKET)  
9.875.9042.059-2  
LEIPZIGER LEUCHTEN



recom. pole height: 4.00m – 6.00m light standards: low, medium and high lighting requirements lamp: excl. metal halide, sodium, compact fluorescent lamps; incl. CosmoPolis; incl. 1 glare-free LLM LED module 1 , easy to replace colour temperature: 2.800K, 3.000K warm white or 4.000K neutral white gear: HCI and NAV: incl. low loss ballast, ignitor and condensor; electronic ballast on request; CDO, CPO, compact fluorescent lamps: incl. electronic ballast; LED: electronic driver up to 100.000 hours; LED: CLO mode LED life expectancy: up to 50.000 hours/ L100 light control: at extra cost: dimming; power reduction; LED: CLEVER LIGHT 10 optical system: reflector system for directed, horizontally mounted ellipsoid, coated lamps (except for CPO); LED: reflector system for directed, horizontally mounted LLM LED modules light distribution: asymmetrical wide beam; LLM LED: extreme wide beam luminaire head: made of aluminium with a special white, reflective underside finish; powder coated bracket: incl. decorative semicircular bracket for post tops resp. WL: made of stainless steel, with wall shield made of aluminium, powder coated colour: RAL or DB glazing: polycarbonate, clear or pearl structured, impact resistant, UV-stabilised, wiring: NADJA: via a clamp within the luminaire head; NADJA /1: luminaire head completely wired; via a plug and socket connector outside the luminaire head installation: for post top  $\varnothing$  76mm; NADJA V, V/1: for tubular column only; WL: to be screwed to the wall accessory: lamp (except CPO, LED), cable, column, pole accessories, wall fixing materials – to be ordered separately application areas: residential and local distribution roads, car parks, schools, hotels, factory premises, paths, squares, parks

## Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	31 W	CRI	70
Total flux	2725 lm	LOR	100%
Luminous efficacy	88 lm/W	ULOR	2%
		Total power	31 W

## Mounting mode

Pole top mounted

## Shape and measurements

Height: 20.08 in  
Diameter: 20.08 in

## Adjustability

Height adjustable

## Design

Material impression: Matt, Plastic  
Color of housing: White

## Glare protection

Glare protection: UGR < 19

## Electric

System power: 31 W  
Ballast: ECG

## Integrated sensors

Integrated sensors: Motion sensor

## Protection

IP: 65  
Designation labels: CE

#### Other operating numbers

Ambient temperature range: 14...95°F