## Product data sheet

CLARA III (W. REFLECTOR FOR T-LAMPS) 9.763.2032.15

LEIPZIGER LEUCHTEN








For medium/high light requirements, mounting height 4.00 – 7.00 m. - Impact-resistant clear/opal polycarbonate attachment,UV- stabilized - High-pressure lamps with coated bulbs use reflector lamellae made of premium highest-grade aluminium, burnishid and anodized, for light guidance and glare limitation - Computer-optimized reflector system for high-pressure lamps with clear glass tubular bulbs ensures excellent illumination - Aluminium reflector finished in special white paint for max. light reflection - Corrosion-resistant cast aluminium unit carrier, painted - All electrical components on one block - Adapter jack connection -Available in any RAL or DB colour without surcharge - for post dia. 76mm; order separately Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

## Light output 1



|  | 1 | x Hiah | pressure | sodium | vapour | lamp |
|--|---|--------|----------|--------|--------|------|
|--|---|--------|----------|--------|--------|------|

| Nominal lamp power | 70 W    | LOR         | 82%     |
|--------------------|---------|-------------|---------|
| Lamp flux          | 6600 lm | ULOR        | 5%      |
| Luminous efficacy  | 65 lm/W | Total flux  | 5422 lm |
| CCT                | 2000 K  | Total power | 83 W    |
| CRI                | 25      |             |         |

Mounting mode

Pole top mounted

Shape and measurements

Height: 23.62 in Diameter: 29.92 in Electric

System power: 83 W

Protection

IP: 55