

# Product data sheet


KTRIBE F3 CRO/ALL.BRO.  
F6301046  
FLOS



IP  
20

Floor lamp providing diffused lighting. Base, rod support and diffuser support in die-cast, polished Zamak alloy. Rod in polished aluminum. Injection-molded PC (polycarbonate) opal inner diffuser and support for the lamp-holder. Outer diffusers in plissé cloth, transparent PMMA (polymethylmethacrylate), silver or bronze on the inner surface, by vacuum aluminum coating. Injection-molded PC (polycarbonate) upper ring, completely transparent, or transparent brown for the outer bronze diffuser. Resistive dimmer wired on cord for 0-100% light adjustment. FEP/PVC, UV-stabilized transparent power cord length 1500 mm. Net weight 14 kg

## Light output 1



### 1 x Halogen low voltage lamp without reflector

Nominal lamp power	230 W	Socket	E27
Lamp flux	4210 lm	LOR	15%
Luminous efficacy	3 lm/W	ULOR	7%
CCT	2821 K	Total flux	623 lm
CRI	99	Total power	230 W

## Mounting mode

Standing / Bollard, Floor mounted

## Shape and measurements

Length: 21.65 in  
Width: 21.65 in  
Height: 72.05 in

## Adjustability

Fixed

## Electric

System power: 230 W

## Protection

IP: 20