Product data sheet

NADJA VII (2-ARMED) 9.877.3062.85

LEIPZIGER LEUCHTEN








Recommended mounting height 3.50 - 5.00 m, other heights please inquire. - High-quality mirror optics guarantee excellent illumination and glare protection - All designs to suit non-glare class KB1 - Aluminium luminaire body, inside white, outside painted in colour - Aluminium unit carrier, painted white - Special reflector made of highest grade aluminium, burnished, anodized - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded -Available in any RAL or DB colour without surcharge - Scope of supply includes painted special steel brackets - please order pole dia. 60 mm separately Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet


Light output 1



1 x High pressure mercury vapour lamp		
Nominal lamp power	125 W	
Lamp flux	6800 lm	
Luminous efficacy	39 lm/W	
CCT	3400 K	
CRI	54	

LOR	78%
Total flux	5317 lm
Total power	137 W

Light output 2



1 x High pressure mercury vapour lamp			
Nominal lamp power	125 W	LOR	
Lamp flux	6800 lm	Total flux	
Luminous efficacy	39 lm/W	Total power	
CCT	3400 K		
CRI	54		

Mounting mode Electric

Pole top mounted System power: 274 W

Shape and measurements Protection

Height: 16.54 in IP: 55

Diameter: 16.54 in

78% 5317 lm 137 W