

Product data sheet


投光灯
PAK470100 PAK-L03-250L-AE-LJ
PAK




IP
65

高压铸铝3MM壁厚外壳 高纯度阳极铝材料旋转设计反射器，投射距离远，效率高，安全钢化玻璃保护罩，采用硅胶密封圈，提高防护效果。
防护等级：IP65 适用光源：金卤灯 250W 适用于大型广告牌、工厂大楼、仓库、运动场、大型商场和高层建筑物立面等照明。

Light output 1



1 x Metal halide lamp			
Nominal lamp power	250 W	Socket	E40
Lamp flux	22700 lm	LOR	75%
Luminous efficacy	64 lm/W	Total flux	17081 lm
CCT	4000 K	Total power	267.7 W
CRI	65		



1 x Metal halide lamp			
Nominal lamp power	250 W	Socket	E40
Lamp flux	24200 lm	LOR	75%
Luminous efficacy	68 lm/W	Total flux	18210 lm
CCT	4000 K	Total power	267.7 W
CRI	70		

Mounting mode

Pole top mounted, Floor mounted

Shape and measurements

Length: 7.46 in
Width: 11.13 in
Height: 11.78 in

Adjustability

Tiltable

Electric

System power: 267.7 W

Protection

IP: 65