Product data sheet

VOLKMAR III (2-ARMED) 9.870.0228.00

LEIPZIGER LEUCHTEN








For medium light requirements, mounting heights from 3.00 - 4.00 m. - Excellent uniform illumination, optimal glare protection - Mirror lamellae for light guidance and glare limitation made of premium highest grade aluminium, burnished and anodized - Luminaire body made of aluminium/galvanized steel sheet - Impact-resistant clear polycarbonate attachment, UV-stabilized - Steel tubing galvanized and painted -Adapter jack connection -Available in any RAL or DB colour without surcharge -Order pole for single-bracket luminaire, dia. 60 mm, separately -Order pole for multi-bracket luminaire, dia. 76 mm, separately Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensated

Light output 1




1 x High pressure sodium vapour lamp Nominal lamp power 100 W

Lamp flux 10400 lm Luminous efficacy 49 lm/W CCT 2000 K CRI 25

LOR 55% ULOR 15% Total flux 5680 lm Total power 115 W

Light output 2



1 x High pressure sodium vapour lamp

| J 1 | | | |
|--------------------|----------|-------------|---------|
| Nominal lamp power | 100 W | LOR | 55% |
| Lamp flux | 10400 lm | ULOR | 15% |
| Luminous efficacy | 49 lm/W | Total flux | 5680 lm |
| CCT | 2000 K | Total power | 115 W |
| CRI | 25 | | |

Mounting mode

Pole top mounted

Shape and measurements

Height: 28.35 in Diameter: 16.14 in Electric

System power: 230 W

Protection

IP: 55