

# Product data sheet

DIETER II  
9.894.3142.05  
LEIPZIGER LEUCHTEN



IP  
65


Recommended mounting height 4.00 - 5.00 m. - Impact-resistant clear polycarbonate cylinder, UV-stabilized - Special steel frame, painted - Large aluminium reflector, underside finished in special white paint for max. light reflection - Mirror lamellae for light guidance and glare limitation made of premium highest grade aluminium, burnished and anodized - All electrical components on one block - Adapter jack connection - Lamps are easy to change - Available in any RAL or DB color without surcharge - Please order pole mount dia. 76 mm separately  
Voltage: 230V 50Hz Protected to: IP 65 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensated

## Light output 1



### 1 x High pressure mercury vapour lamp

Nominal lamp power	50 W	LOR	52%
Lamp flux	2000 lm	ULOR	13%
Luminous efficacy	18 lm/W	Total flux	1035 lm
CCT	3400 K	Total power	59 W
CRI	54		



### 1 x High pressure mercury vapour lamp

Nominal lamp power	80 W	LOR	52%
Lamp flux	4000 lm	ULOR	13%
Luminous efficacy	23 lm/W	Total flux	2070 lm
CCT	3400 K	Total power	89 W
CRI	54		

## Mounting mode

Pole top mounted

## Shape and measurements

Height: 19.69 in  
Diameter: 10.63 in

## Electric

System power: 59-89 W

## Protection

IP: 65