


Product data sheet

ALU-STAR MIDI
721807.0031
RZB



Series: ALU-STAR midi High efficient LED outdoor floodlight. Housing made of corrosion-resistant die-cast aluminium, seawater resistant powder-coated. Thermally decoupled driver compartment, integral driver. With membrane valve as a standard to avoid condensed water. Rotation-symmetric reflector made of reflex-boosted MIRO-SILVER. Cover clear single-pane toughened glass. Spot, narrow beam. COB LED with socket for easy replacement. Stainless steel fixing clips with compensation for drill hole deviations. Rotation angle can be adjusted and locked in 3,6° steps, tilt angle in 5° steps with angular scale. Piano-key terminal up to 28x5x2,5 mm², max cable Ø 13mm, comes with second cable gland for loop through. Colour: anthracite metallic (DB703) Length: 255mm Width: 240mm Height: 255mm Lamp: LED System power: 57W Rated luminous flux: 5100lm Luminous efficiency: 89lm/W Control gear: Regulated power supply Protection class: I Type of protection: IP65

Light output 1 (integrated)



| | | | |
|--------------------|---------|-------------|--------|
| Lamp type | LED | CCT | 3000 K |
| Nominal lamp power | 57 W | CRI | 80 |
| Total flux | 5100 lm | LOR | 100% |
| Luminous efficacy | 89 lm/W | Total power | 57 W |

Mounting mode

Standing / Bollard, Pole integrated

Shape and measurements

Length: 9.45 in
Width: 10.04 in
Height: 10.04 in

Adjustability

Tiltable

Electric

System power: 57 W

Protection

IP: 65
IK: 07