Product data sheet

LUCAS I (WALL FITTING BEADED) 9.835.3066.16 LEIPZIGER LEUCHTEN




Mounting heights between 4.00 - 6.00 m. - High-quality mirror optics to suit non-glare class KB1 - Aluminium cast luminaire body, inside white, outside painted in colour - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Luminaires with wiring ready for connection - Easy installation with adapter jack - Scope of supply includes complete unit with one/two painted special steel brackets -Available in any RAL or DB colour without surcharge Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

IP 55

CRI

Light output 1



1 x High pressure mercury vapour lamp					
Nominal lamp power	125 W	LOR			
Lamp flux	6800 lm	ULOR			
Luminous efficacy	41 lm/W	Total flux			
CCT	3400 K	Total power			

54

1434	"YAH
1 A	
KK+	+>b>
$\times \times $	
+	-t

1 x High pressure mercury vapour lamp					
Nominal lamp power	80 W	LOR	83%		
Lamp flux	4000 lm	ULOR	2%		
Luminous efficacy	37 lm/W	Total flux	3316 lm		
CCT	3400 K	Total power	89 W		
CRI	54				

Mounting mode Wall mounted Shape and measurements

Height: 22.44 in Diameter: 22.44 in

Electric

System power: 89-137 W

Protection

IP: 55

83%

2%

5637 lm 137 W