

Product data sheet


FRIEDER I
6.115.1072.01
LEIPZIGER LEUCHTEN



IP
65


recom. pole height: 3.50m - 12.00m light standards: low, medium and high lighting requirements lamp: excl. halogen, metal halide or sodium lamp gear: HCL and NAV: incl. low loss ballast, ignitor and condensor; electronic ballast on request light control: at extra cost: power reduction, dimming optical system: computer-optimised reflector system for clear, tubular lamps light distribution: asymmetrical luminaire head: made of die cast aluminium, powder coated bracket: with short bracket or wall bracket with wall shield made of hot dip galvanised steel, powder coated colour: RAL 7043 (traffic grey) glazing: flat, clear toughened glass glazing, to be hinged down wiring: completely wired; via a clamp within the luminaire head installation: for top entry \varnothing 76mm accessory: lamp, cable, cable junction box, column, pole accessories – to be ordered separately application areas: parkways, schools, home for elderly people, hotels, factory premises, paths, squares, car parks

Light output 1



1 x High pressure sodium vapour lamp

Nominal lamp power	150 W	LOR	64%
Lamp flux	15000 lm	Total flux	9535 lm
Luminous efficacy	56 lm/W	Total power	170 W
CCT	2000 K		
CRI	25		



1 x Metal halide lamp

Nominal lamp power	150 W	LOR	64%
Lamp flux	15000 lm	Total flux	9535 lm
Luminous efficacy	56 lm/W	Total power	170 W
CCT	3000 K		
CRI	90		

Mounting mode

Pole top mounted

Electric

System power: 170 W

Shape and measurements

Length: 12.99 in

Width: 11.02 in

Height: 4.13 in

Protection

IP: 65

Adjustability

Height adjustable