Product data sheet

VOLKMAR III (WALL FITTING) 9.840.0089.00

LEIPZIGER LEUCHTEN









For medium light requirements, mounting heights from 3.00 - 4.00 m. - Excellent uniform illumination, optimal glare protection - Mirror lamellae for light guidance and glare limitation made of premium highest grade aluminium, burnished and anodized - Luminaire body made of aluminium/galvanized steel sheet - Impact-resistant clear polycarbonate attachment, UV-stabilized - Steel tubing galvanized and painted - Adapter jack connection -Available in any RAL or DB colour without surcharge Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensated

Light output 1



| 1 x High pressure mercury v | apour lamp |
|-----------------------------|------------|
| Nominal lamp power | 50 W |
| Lamp flux | 2000 lm |
| Luminous efficacy | 19 lm/W |
| CCT | 3400 k |
| CRI | 54 |
| | |

| LOR | 55% |
|-------------|---------|
| ULOR | 15% |
| Total flux | 1092 lm |
| Total power | 59 W |
| | |



| i x High pressure mercury vapour lamp | | | | | |
|---------------------------------------|---------|-------------|---------|--|--|
| Nominal lamp power | 80 W | LOR | 55% | | |
| Lamp flux | 4000 lm | ULOR | 15% | | |
| Luminous efficacy | 25 lm/W | Total flux | 2185 lm | | |
| CCT | 3400 K | Total power | 89 W | | |
| CRI | 54 | | | | |

Mounting mode

Wall mounted

Shape and measurements

Height: 16.14 in Diameter: 16.14 in Electric

System power: 59-89 W

Protection

IP: 55