

# Product data sheet

RICHARD II (WALL FITTING)  
9.844.3046.00  
LEIPZIGER LEUCHTEN




Mounting height approx. 3,00 - 4,50 m, for medium light requirements. - Impact-resistant clear polycarbonate cylinder, UV-stabilized - Circular shield for glare limitation made of anodized aluminium - Large aluminium reflector, inside finished in special white paint for max. light reflection - Aluminium cover, painted - Unit carrier made of corrosion-resistant cast aluminium, painted - All electrical components are arranged on a block - Connection with adapter jack -Available in any RAL or DB colour without surcharge Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

## Light output 1



1 x High pressure mercury vapour lamp			
Nominal lamp power	50 W	LOR	43%
Lamp flux	2000 lm	ULOR	8%
Luminous efficacy	15 lm/W	Total flux	860 lm
CCT	3400 K	Total power	59 W
CRI	54		



1 x High pressure mercury vapour lamp			
Nominal lamp power	80 W	LOR	43%
Lamp flux	4000 lm	ULOR	8%
Luminous efficacy	19 lm/W	Total flux	1719 lm
CCT	3400 K	Total power	89 W
CRI	54		

## Mounting mode

Wall mounted

## Shape and measurements

Height: 9.84 in  
Diameter: 9.84 in

## Electric

System power: 59-89 W

## Protection

IP: 55