

Product data sheet

NORA I (WALL FITTING BEADED)
9.741.3046.06
LEIPZIGER LEUCHTEN



IP
55

For medium light requirements, mounting height 3.50 - 4.00 m. - Impact-resistant clear or beaded polycarbonate attachment, UV-stabilized - Special reflector of premium highest-grade aluminium, burnished and anodized, for excellent illumination and glare protection -Aluminium luminaire body, inside finished in white paint, outside painted in colour - Aluminium unit carrier, painted white - Adapter jack connection - Available in any RAL or DB colour without surcharge - Scope of delivery includes special steel post/wall-mounted bracket, painted Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

Light output 1



1 x High pressure mercury vapour lamp

Nominal lamp power	50 W	LOR	73%
Lamp flux	2000 lm	ULOR	3%
Luminous efficacy	25 lm/W	Total flux	1464 lm
CCT	3400 K	Total power	59 W
CRI	54		



1 x High pressure mercury vapour lamp

Nominal lamp power	80 W	LOR	73%
Lamp flux	4000 lm	ULOR	3%
Luminous efficacy	33 lm/W	Total flux	2927 lm
CCT	3400 K	Total power	89 W
CRI	54		

Mounting mode

Wall mounted

Shape and measurements

Height: 21.26 in
Diameter: 21.26 in

Electric

System power: 59-89 W

Protection

IP: 55