

Product data sheet

RICHARD I (1-ARMED)
9.890.3046.00
LEIPZIGER LEUCHTEN




Mounting height approx. 3.00 - 4.50 m, for medium light requirements. - Impact-resistant clear polycarbonate cylinder, UV-stablized - Mirror lamellae for light guidance and glare limitation made of premium highest-grade aluminium, burnished and anodized - Aluminium reflector finished in special white paint for max. light reflection - Aluminium cover painted - Unit carrier made of corrosion-resistant cast aluminium, painted - All electrical components arranged on a block - Connection with adapter jack - Available in any RAL or DB colour without surcharge - Order pole, dia. 60 mm, separately, order pole for double-bracket luminaire, dia. 76 mm, separately Wall luminaires Richard BI and BII as described above, except -Wall luminaire BI with opal cylinder, no mirror lamellae - Reflector made of impact-resistant RESIST plexiglas, inside finished in white paint, outside painted in colour Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

Light output 1



1 x High pressure mercury vapour lamp

Nominal lamp power	50 W	LOR	59%
Lamp flux	2000 lm	ULOR	15%
Luminous efficacy	20 lm/W	Total flux	1183 lm
CCT	3400 K	Total power	59 W
CRI	54		



1 x High pressure mercury vapour lamp

Nominal lamp power	80 W	LOR	59%
Lamp flux	4000 lm	ULOR	15%
Luminous efficacy	27 lm/W	Total flux	2367 lm
CCT	3400 K	Total power	89 W
CRI	54		

Mounting mode

Pole top mounted

Shape and measurements

Height: 24.21 in

Diameter: 9.84 in

Electric

System power: 59-89 W

Protection

IP: 55

Designation labels: CE, ENEC, F