


Product data sheet

MEGA SONIC GEAR-ARM
5936-7-3-753-XX
UNILAMP




The SONIC family of spot and floodlight are available as ground or wall mount with outrigger arms setting, extended standing form, pole clamp and wall clamp setting, indirect pole light and wall light. There are wide ranges of accessories available; spreader lens, glare shield unit, tree strap, earth spike and anchor bolt kit. Available in three (3) sizes with a choice of five (5) colors. SONIC is operated with high power LED in COB technology. Manufactured to eliminate dust and water gathering over the lens the front cover sits perfectly flush. High efficiency reflectors and lens' are used in this luminaire family. Calibrated aiming positions assist with locating the beam spread perfectly. For ease of installation and thermal issues the control gear compartment is housed separately to the lamp. Wherever the need for highlighting of sculptures, walls, building facades SONIC is a first choice option. Spec • Designed, Manufactured and Tested according to IEC 60598-1, IEC 60598-2-1 and VDE regulations. • LM6 Die Cast Aluminium and Extruded Aluminium body. • Stainless steel screws. • Nano Ceramic surface conversion. • Double layer coating. • Safety glass cover. • Post-cured silicone gasket. • High quality LED module and driver. • High efficiency reflector. • Adjustable optic. • GFR PA6.6 terminal block. • Weather proof TPE grommet or M20 Cable gland. • Installation work has to be carried on according to the enclosed product manual.

Light output 1



1 x Metal halide lamp			
Nominal lamp power	150 W	Socket	G12
Lamp flux	14500 lm	LOR	36%
Luminous efficacy	97 lm/W	Total flux	5162 lm
CCT	4200 K	Total power	170 W
CRI	98		



1 x Metal halide lamp			
Nominal lamp power	150 W	Socket	G12
Lamp flux	14500 lm	LOR	36%
Luminous efficacy	97 lm/W	Total flux	5162 lm
CCT	3000 K	Total power	170 W
CRI	84		

Mounting mode

Wall mounted

Electric

System power: 170 W
Appliance Class: I

Shape and measurements

Length: 5.35 in

Width: 40.58 in

Height: 8.11 in

Adjustability

Rotatable, Tilttable

Protection

IP: 65

IK: 06