


Product data sheet

投光灯

PAK473101 PAK-L07-150A-AE-L


PAK



IP
65

高压铸铝成型外壳，5MM钢化玻璃，反射罩采用高纯阳极电镀铝，安全活页装置，四角下压式锁扣设计，安装方便；U型承托镀锌防锈支架，安装方便，可调角度，优质硅胶耐高温，防水密封圈。防护等级：IP65 适用光源：金卤灯/高压钠灯 150W 适用于建筑泛光照明、广告招牌照明、体育馆、货场、码头、车场等照明。


Light output 1



1 x High pressure sodium vapour lamp

Nominal lamp power	150 W
Lamp flux	15000 lm
Luminous efficacy	62 lm/W
CCT	2000 K
CRI	31

Socket	Rx7S
LOR	69%
Total flux	10371 lm
Total power	166.7 W



1 x Metal halide lamp

Nominal lamp power	150 W
Lamp flux	13500 lm
Luminous efficacy	56 lm/W
CCT	4000 K
CRI	80

Socket	Rx7S
LOR	69%
Total flux	9334 lm
Total power	166.7 W

Mounting mode

Pole top mounted, Floor mounted

Shape and measurements

Length: 8.00 in
Width: 12.45 in
Height: 5.46 in

Adjustability

Tiltable

Electric

System power: 166.7 W

Protection

IP: 65