Product data sheet

VOLKMAR I (WALL FITTING) 9.840.0089.08

LEIPZIGER LEUCHTEN









For medium light requirements, mounting heights from 3.00 - 4.00 m. - Excellent uniform illumination, optimal glare protection - Luminaire body made of aluminium/galvanized steel sheet - Impact-resistant opal polyethylene attachment, UV-stabilized - Steel tubing galvanized and painted - Adapter jack connection -Available in any RAL or DB colour without surcharge Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensated

Light output 1



1 x High pressure mercury vapour lamp				
Nominal lamp power	50 W	LOR		
Lamp flux	2000 lm	ULOR		
Luminous efficacy	25 lm/W	Total flux		
CCT	3400 K	Total power		
CRI	54			



1 x High pressure mercury vapour lamp				
Nominal lamp power	80 W	LOR	73%	
Lamp flux	4000 lm	ULOR	28%	
Luminous efficacy	33 lm/W	Total flux	2908 lm	
CCT	3400 K	Total power	89 W	
CBI	54			

Mounting mode

Wall mounted

Shape and measurements

Height: 16.14 in Diameter: 16.14 in Electric

System power: 59-89 W

Protection

IP: 55

73% 28% 1454 lm 59 W