

Product data sheet


RICHARD BI (FLOWER BED FITTING)
9.880.5521.00
LEIPZIGER LEUCHTEN



IP
55

Decorative luminaire for lanes, driveways, terraces, gardens, and for night illumination and hazardous areas. - Impact-resistant clear/opal polycarbonate cylinder, UV-stabilized - Mirror lamellae for Richard BII made of burnished, anodized highest-grade aluminium - Reflector made of impact-resistant RESIST plexiglass, inside finished in white paint, outside painted in colour - Unit carrier made of corrosion-resistant cast aluminium, painted - Upright tube made of special steel, painted - Available in any RAL or DB colour without surcharge Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

Light output 1



| | | | |
|------------------------------|---------|-------------|--------|
| 1 x Compact fluorescent lamp | | | |
| Nominal lamp power | 23 W | LOR | 39% |
| Lamp flux | 1500 lm | ULOR | 13% |
| Luminous efficacy | 26 lm/W | Total flux | 588 lm |
| CCT | 2571 K | Total power | 23 W |
| CRI | 90 | | |

Mounting mode

Standing / Bollard

Shape and measurements

Height: 11.42 in
Diameter: 7.09 in

Electric

System power: 23 W

Protection

IP: 55