


# Product data sheet

PURE 3 DOWNLIGHT  
09.1810/QR-111/75W/24°45°  
FLOS




Recessed luminaire for indoor application. For very low voltage halogen lamps or standard and discharge lamps. Self-extinguishing ceramic or engineering plastic lamp holders, with single-pole, transparent electric wires with double Teflon insulation.

## Light output 1



### 1 x Halogen low voltage lamp without reflector

|                    |        |             |        |
|--------------------|--------|-------------|--------|
| Nominal lamp power | 75 W   | Socket      | G53    |
| Lamp flux          | 707 lm | LOR         | 100%   |
| Luminous efficacy  | 9 lm/W | Total flux  | 708 lm |
| CCT                | 3000 K | Total power | 75 W   |
| CRI                | 99     |             |        |



### 1 x Halogen low voltage lamp without reflector

|                    |         |             |        |
|--------------------|---------|-------------|--------|
| Nominal lamp power | 75 W    | Socket      | G53    |
| Lamp flux          | 871 lm  | LOR         | 100%   |
| Luminous efficacy  | 12 lm/W | Total flux  | 873 lm |
| CCT                | 3000 K  | Total power | 75 W   |
| CRI                | 99      |             |        |

## Mounting mode

Ceiling recessed

## Shape and measurements

Length: 5.91 in

Width: 5.91 in

Height: 5.51 in

## Adjustability

Rotatable, Tilttable

## Electric

System power: 75 W

Appliance Class: III

## Protection

IP: 20