

Product data sheet

NADJA III (WALL FITTING BEADED)
9.846.3162.06
LEIPZIGER LEUCHTEN



IP
55

Recommended mounting height 3.50 - 5.00 m, other heights please inquire. - High-quality mirror optics guarantee excellent illumination and glare protection - All designs to suit non-glare class KB1 - Aluminium luminaire body, inside white, outside painted in colour - Aluminium unit carrier, painted white - Special reflector made of highest grade aluminium, burnished, anodized - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Available in any RAL or DB colour without surcharge Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet


Light output 1



1 x High pressure mercury vapour lamp

Nominal lamp power	125 W
Lamp flux	6800 lm
Luminous efficacy	39 lm/W
CCT	3400 K
CRI	54

LOR	78%
Total flux	5302 lm
Total power	137 W



1 x High pressure mercury vapour lamp

Nominal lamp power	80 W
Lamp flux	4000 lm
Luminous efficacy	35 lm/W
CCT	3400 K
CRI	54

LOR	78%
Total flux	3119 lm
Total power	89 W

Mounting mode

Wall mounted

Shape and measurements

Height: 16.54 in
Diameter: 16.54 in

Electric

System power: 89-137 W

Protection

IP: 55