Product data sheet

SCAPHA 311992.004.1.76

RZB








Series: SCAPHA Pendant luminaire with elliptical shape. Base: aluminium, powder-coated. Canopy and glass fixture steel powder-coated. Handmade concave glass, matt finish on the outside, painted white on the inside. Uniform and glare-free illumination of the small boat shaped corpus by specially adapted LED panel boards. Suitable for pendant. 2-point steel cable suspension, steplessly adjustable. Special lengths available on request. TouchDim sensor capable. Light and/or presence sensors can be integrated. Colour: silver, metallic Length: 1264 mm Width: 174 mm Height: 66.5 mm Suspension length: 500-1200 mm Lamp: LED Socket: without socket Colour temperature: 4000K Colour rendering index (CRI): 80 System power: 51 W Rated luminous flux: 3550 lm Luminous efficiency: 70 lm/W Control gear: Converter, dimmable, DALI Protection class: I Type of protection: IP 20

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	51 W	CRI	80
Total flux	3550 lm	LOR	100%
Luminous efficacy	70 lm/W	ULOR	11%
		Total power	51 W

Mounting mode

Pendant

Shape and measurements

Length: 6.85 in Width: 49.76 in Height: 2.64 in

Adjustability

Fixed

Electric

System power: 51 W

Protection

IP: 20