


# Product data sheet

ICON MINI OPAL POST LED 3000K 47W ASYM POLISH POS1 SIDE CLO  
5747812844  
LOUIS POULSEN



LP Icon Mini Opal Post Design by: Mads Odgård Concept : The fixture provides mainly direct downward illumination. The shade is lit up from within and creates a soft diffuse upwards light. Depending on the choice of reflector, the downward lighting characteristics will vary. The reflector types have been designed in different variations to provide either asymmetrical or symmetrical distributions of light. Finish : Aluminium coloured with textured surface, powder coated. Materials: Shade: High pressure moulded white opal acrylic. Reflector: Metallized, high pressure moulded polycarbonate. Diffuser LED: Toughened clear glass with silk screen print. Housing: Die cast aluminium. Mounting : Fitting/pipe stub dimensions: Ø 48mm or wire suspension. Installation cable: Sidemounted version: 9m, 3x1,5mm<sup>2</sup> (Class I) or 9m, 2x1,5mm<sup>2</sup> (Class II). Topmounted version: No cable. Terminal block: 1x3x2.5mm<sup>2</sup>. Terminal block positioning: In fixture head. Looping: Approved in topmounted variant, max. 3x1,5mm<sup>2</sup>. Ballast positioning: In fixture head. Class: Ingress protection IP66. Electric shock protection I w. ground, II w/o ground. IK06. Sizes and weights: Width x Height x Length (mm) 476 x 422 x 476 Max 10.4 kg

## Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	47 W	CRI	80
Total flux	4650 lm	LOR	100%
Luminous efficacy	99 lm/W	Total power	47 W

## Mounting mode

Pole top mounted

## Shape and measurements

Height: 15.75 in

Diameter: 18.70 in

## Adjustability

Fixed

## Electric

System power: 47 W

Appliance Class: II

## Protection

IP: 66

IK: 06