# Product data sheet

CLARA III (CLEAR ATTACHMENT) 9.763.3042.05

LEIPZIGER LEUCHTEN








For medium/high light requirements, mounting height 4.00 – 7.00 m. - Impact-resistant clear/opal polycarbonate attachment,UV- stabilized - High-pressure lamps with coated bulbs use reflector lamellae made of premium highest-grade aluminium, burnishid and anodized, for light guidance and glare limitation - Computer-optimized reflector system for high-pressure lamps with clear glass tubular bulbs ensures excellent illumination - Aluminium reflector finished in special white paint for max. light reflection - Corrosion-resistant cast aluminium unit carrier, painted - All electrical components on one block - Adapter jack connection -Available in any RAL or DB colour without surcharge - for post dia. 76mm; order separately Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

#### Light output 1



1 x High pressure mercury	vapour lamp
Nominal lamp power	80 W
Lamp flux	4000 lm
Luminous efficacy	23 lm/\//

Luminous efficacy 23 lm/W CCT 3400 K CRI 54

LOR 51% ULOR 9%

Total flux 2059 lm
Total power 89 W

#### Mounting mode

Pole top mounted

## Shape and measurements

Height: 23.62 in Diameter: 29.92 in

#### Electric

System power: 89 W

## Protection

IP: 55