


Product data sheet

GEMMA
342815
FLOS



• Recessed round luminaire for outdoor installation in the ground. • Configuration: die-cast aluminium structure. EN AB-47100 alloy (low copper content). • Double layer coating for high resistance to corrosion: The low copper Aluminium alloy is painted with a double coat using powders which are compliant with QUALICOAT standards: a first layer of epoxy powder (with excellent chemical and mechanical resistance) and a second finishing layer of polyester powder (resistant to UV rays and atmospheric agents). The entire painting process of the aluminium fitting starts from components which have been sand-blasted in advance to make the surface more porous and increase the adherence of the paint. Ares effects alkaline and acid washing to clean the surfaces completely, then rinses with demineralised water to remove any residue particles, subsequently a chemical conversion treatment is done to protect against rusting.

Light output 1



1 x Halogen low voltage lamp without reflector			
Nominal lamp power	50 W	Socket	Gz10
Lamp flux	1200 lm	LOR	71%
Luminous efficacy	17 lm/W	ULOR	71%
CCT	2900 K	Total flux	852 lm
CRI	100	Total power	50 W

Mounting mode

Floor recessed

Shape and measurements

Height: 9.53 in
Diameter: 7.09 in

Adjustability

Tiltable

Electric

System power: 50 W
Appliance Class: I

Protection

IP: 67
IK: 09