
Product data sheet

LP CIRCLE SURFACE MOUNTED Ø450 WHITE LED 4000K 25W 5742583495


LOUIS POULSEN





LP Circle Surface Mounted Design: Mikkel Beedholm/KHR arkitekter Concept: The fixture emits diffuse light via a high-efficiency acrylic diffuser. The diffuser, which is encircled by a voluminous coloured or white ring, is hidden when viewed from low angles. Angling the inner side of the reflector ring 5° creates a comfortable and decorative graduation of the light from the diffuser. The luminaire ,floats' 34 mm below the ceiling, creating a visual lightness. Finish: White, Black, Pale Petroleum or Yellow. Powder coated. Material: Reflector: Extruded aluminium. Diffuser: Acrylic, frosted. Top: Aluminium. Mounting: Directly on ceiling. Built-in driver. Terminal strip: 5x1.5mm2. Looping: Approved, max 5x1.5mm2. Cable entries: Rear, Side-mounted. Weight: Min: 2.4 kg Max: 5.0 kg Class: Ingress protection IP20. Electric shock protection I.

Light output 1 (integrated)



Lamp type Nominal lamp power Total flux Luminous efficacy

LED	
25 W	
2793 lm	
112 lm/W	

CCT

CRI

LOR

Total power

4000 K

90

100%

25 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 17.95 in Width: 17.95 in Height: 5.51 in

Adjustability

Fixed

Electric

System power: 25 W Appliance Class: I

Protection

IP: 20