

Product data sheet


ROMEO OUTDOOR C1 GRI FLUO
F6450020
FLOS



IP
55


Ceiling luminaires for outdoor use providing direct and diffused light. Die-cast aluminum alloy wall or ceiling fitting with brilliant finish. Injection-molded polycarbonate (PC) cover rose. 316L stainless steel stem-polished. Opal-colored, vacuum-formed internal polycarbonate diffuser. Diffuser support in injection-molded opal colored polycarbonate. Crown support in injection-molded opal-colored polycarbonate. Two-color vacuum-formed engineering plastic outer crowns

Light output 1



1 x Compact fluorescent lamp

Nominal lamp power	18 W	Socket	Gx24Q-2
Lamp flux	1200 lm	LOR	47%
Luminous efficacy	32 lm/W	ULOR	4%
CCT	4000 K	Total flux	568 lm
CRI	80	Total power	18 W



1 x Compact fluorescent lamp

Nominal lamp power	18 W	Socket	Gx24Q-2
Lamp flux	1200 lm	LOR	47%
Luminous efficacy	32 lm/W	ULOR	4%
CCT	3000 K	Total flux	568 lm
CRI	84	Total power	18 W

Mounting mode

Pendant

Shape and measurements

Length: 13.39 in

Width: 13.39 in

Height: 8.82 in

Adjustability

Fixed

Electric

System power: 18 W

Protection

IP: 55