
Product data sheet


LUCAS IV (1-ARMED) 9.854.2072.15 LEIPZIGER LEUCHTEN





Mounting heights between 4.00 - 6.00 m. - High-quality mirror optics to suit non-glare class KB1 - Aluminium cast luminaire body, inside white, outside painted in colour - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Luminaires with wiring ready for connection - Easy installation with adapter jack - Scope of supply includes complete unit with one/two painted special steel brackets - Available in any RAL or DB colour without surcharge - Pole for single-bracket luminaire: dia. 76 mm, please order separately inquire separately for pole to suit double-bracket luminaire, Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

Light output 1



1 x High pressure sodium vapour lamp

Nominal lamp power
Lamp flux
Luminous efficacy
CCT
CRI

150 W 17000 lm 81 lm/W 2000 K 25 LOR Total flux Total power

84% 14242 lm 176 W

Mounting mode

Pole top mounted

Shape and measurements

Height: 19.69 in Diameter: 22.44 in

Design

Material impression: Matt Color of housing: White

Electric

System power: 176 W Ballast: ECG Controller: DALI

Protection

IP: 55 Designation labels: CE, ENEC

Other operating numbers

Ambient temperature range: -4...95°F