

Product data sheet


COMPASS SPOT
03.3703/HIT-DE-CRI/70W/102°
FLOS




IP
20

Range of indoor spotlights for accent and general lighting for three-phase track and wall/ceiling installation. Die-cast aluminium alloy, powder-coated optics compartment, diameter 118 mm, composed of an aluminium dissipating element placed above the lamp support, a black thermoplastic screen support ring and 4 mm tempered glass cover. Integrated auxiliary power units for the lamps inside a die-cast aluminium alloy container with powder-coated finish.

Light output 1



1 x Metal halide lamp			
Nominal lamp power	70 W	Socket	Rx7S
Lamp flux	6600 lm	LOR	78%
Luminous efficacy	69 lm/W	Total flux	5162 lm
CCT	3000 K	Total power	75 W
CRI	83		



1 x Metal halide lamp			
Nominal lamp power	70 W	Socket	Rx7S
Lamp flux	5500 lm	LOR	78%
Luminous efficacy	57 lm/W	Total flux	4302 lm
CCT	4200 K	Total power	75 W
CRI	98		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 2.28 in
Width: 4.72 in
Height: 5.83 in

Adjustability

Free

Electric

System power: 75 W

Protection

IP: 20