Product data sheet


DOWNTOWN TRIM EMERGENCY Ø160 03.0226/TC-TEL/26W

FLOS



Luminaires for embedded installation indoor with fluorescent lamps Optical body made in injected aluminium with powder-coated paint finish. Heatsink made in injected aluminium under pressure attached to the body of the luminaire. Lower and upper reflectors available made of anodized aluminium with specular finish. Fixed upper reflector. Inferior reflector formed by self reflector and a spreading lens of 4mm thick and a polycarbonate ring that fixes the reflector to the aluminium ring of the product. Available in two diameters 160mm and 215mm.Luminary with emergency kit for permanent lighting systems using compact fluorescent lamps. Includes combo ballast (inverter+ballast) with Ni-Cd 3hbattery supplied fully connected.

Light output 1



1 x Compact fluorescent lamp

IP 23

| Nominal lamp power | 26 W | Socket | G24Q-2 |
|--------------------|---------|-------------|--------|
| Lamp flux | 1800 lm | LOR | 40% |
| Luminous efficacy | 27 lm/W | Total flux | 713 lm |
| CCT | 3000 K | Total power | 26 W |
| CRI | 84 | | |
| | | | |

W

| Mounting mode | Electric |
|------------------------|------------------|
| Ceiling recessed | System power: 26 |
| Shape and measurements | Protection |
| Height: 6.22 in | IP: 23 |
| Diameter: 6.30 in | |

Adjustability

Fixed