

Product data sheet


LUCAS PVIII (BOLLARD WITH DOOR AND KÜK)
9.882.5307.45
LEIPZIGER LEUCHTEN



IP
55

Decorative luminaire for lanes, driveways, terraces, gardens, and for night illumination and hazardous areas. - Impact-resistant clear/opal polycarbonate cylinder, UV-stabilized - Mirror lamellae for light guidance and glare limitation made of premium highest-grade aluminium, burnished and anodized - Unit carrier, crown flange and ornaments made of corrosion-resistant cast aluminium, painted; ground and passivated special steel parts preferably in jet black, RAL 9005 - Housing/upright tube of special steel painted in any RAL or DB colour without surcharge, or special steel, ground and passivated - All electrical components accommodated on a block -Crown detachable for easy maintenance/lamp change - Upright tube with pole door, incl. cable joint box for cable 5x16 mm² Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711

Light output 1



1 x Compact fluorescent lamp			
Nominal lamp power	18 W	LOR	40%
Lamp flux	1200 lm	ULOR	21%
Luminous efficacy	25 lm/W	Total flux	477 lm
CCT	2899 K	Total power	19 W
CRI	90		

Mounting mode

Standing / Bollard

Electric

System power: 19 W

Shape and measurements

Height: 44.09 in
Diameter: 6.69 in

Protection

IP: 55

Design

Color of housing: Black