Product data sheet

DIETER II (WALL FITTING) 9.839.3162.05

LEIPZIGER LEUCHTEN









Recommended mounting height 4.00 - 5.00 m. - Impact-resistant clear polycarbonate cylinder, UV-stabilized - Special steel frame, painted -Large aluminium reflector, underside finished in special white paint for max. light reflection - Mirror lamellae for light guidance and glare limitation made of premium highest grade aluminium, burnished and anodized - All electrical components on one block - Adapter jack connection - Lamps are easy to change -Available in any RAL or DB color without surcharge Voltage: 230V 50Hz Protected to: IP 65 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensated

Light output 1



1 x High pressure mercu	ıry vapour lamp		
Nominal lamp power	125 W	LOR	52%
Lamp flux	6800 lm	ULOR	13%
Luminous efficacy	26 lm/W	Total flux	3519 lm
CCT	3400 K	Total power	137 W
CRI	54		



I x High pressure mercury	/ vapour lamp		
Nominal lamp power	80 W	LOR	52%
Lamp flux	4000 lm	ULOR	13%
Luminous efficacy	23 lm/W	Total flux	2070 lm
CCT	3400 K	Total power	89 W
CRI	54		

Mounting mode

Wall mounted

Shape and measurements

Height: 10.63 in Diameter: 10.63 in Electric

System power: 89-137 W

Protection

IP: 65