

Product data sheet

AVIATO
741762.003.2
RZB




IP
20

IK
02

Series: Aviato Type of Protection: IP 20 Protection Class: I Voltage: 220 - 240 V / 50 - 60 Hz Housing die-cast aluminium powder-coated, can be rotated 356° horizontally and swivelled 180° vertically, passive cooling, without reflector aluminium faceted, order reflector assembly separately, replaceable LED module, LED included in delivery, with multi-adapter for 3-phase tracks 230V, ceiling mounting. Available Colours: deep black, matt (RAL 9005) Type of Installation: Track on ceiling Dimensions: L 208, B 106, H 237 Lamp: LED Life time: 50000 h (L80/B10) Colour Temperature: 4000K Socket 1: without socket Operating Mode Lamp 1: Regulated power supply Safety Marks: F-mark Impact Protection: IK02 (0,20 Joule) Luminaire flux LED: 2950lm System power: 34W Number of fittings B10A: 15 Number of fittings B16A: 25 Inrush current: 16A EEC: A+

Light output 1 (integrated)



| | | | |
|--------------------|---------|-------------|--------|
| Lamp type | LED | CCT | 4000 K |
| Nominal lamp power | 34 W | CRI | 80 |
| Total flux | 2950 lm | LOR | 100% |
| Luminous efficacy | 87 lm/W | Total power | 34 W |

Mounting mode

Ceiling mounted

Electric

System power: 34 W

Shape and measurements

Length: 4.17 in

Width: 8.19 in

Height: 9.33 in

Protection

IP: 20

IK: 02

Adjustability

Rotatable, Tilttable

Design

Color of housing: Black