

# Product data sheet


ALFONS I FF LED (ASYM. WIDE BEAM)  
9.136.8215.01-3  
LEIPZIGER LEUCHTEN



IP  
66

recom. pole height: 3.00m – 12.00m light standards: low, medium and high lighting requirements lamp: incl. 1, 2, 3 or 4 FF II-X or FF SW-X LED module(s) 7, easy to replace; or incl. LED-10 or LED-15 modules, easy to replace colour temperature: 3.000K warm white or 4.000K neutral white LED gear: electronic driver, up to 100.000 hours; CLO mode LED life expectancy: up to 50.000 hours/L100 light control: at extra cost: FF: power reduction, dimming or CLEVER LIGHT 10 optical system: directed light (multi layer) provided by an exchangeable, anti-aging lens technology light distribution: FF II-X: asymmetrical wide beam; FF SW-X: extreme narrow wide beam; LED-10 and LED-15: depending on the lens combination: symmetrical, asymmetrical or asymmetrical wide beam (s. fig.1; fig. 2) luminaire head: die cast aluminium, powder coated colour: DB 703; other colours on request glazing: flat, clear toughened glass glazing wiring: completely wired; via a plug and socket connector within the luminaire head; luminaire head to be hinged upward installation: for top or side entry; ASA 60 or ASA 76 to be ordered separately: • ASA 60 for side entry ø 48mm up to 60mm (0°, -5°, -10°, -15°) or for top entry ø 60mm (0°, 5°, 10°, 15°) • ASA 76 for top entry ø 76mm (0°, 5°, 10°) accessory: adapter ASA, column, pole accessories, wall bracket, cable – to be ordered separately application areas: parks, boulevards, schools, home for elderly people, hotels, factory premises, residential and local distribution roads, main streets, car parks, pedestrian and cycle lanes, holiday parks

## Light output 1 (integrated)



|                    |          |             |        |
|--------------------|----------|-------------|--------|
| Lamp type          | LED      | CCT         | 3000 K |
| Nominal lamp power | 30 W     | CRI         | 70     |
| Total flux         | 3516 lm  | LOR         | 100%   |
| Luminous efficacy  | 117 lm/W | Total power | 30 W   |

## Mounting mode

Pole integrated, Pole top mounted

## Shape and measurements

Length: 21.65 in  
Width: 9.41 in  
Height: 7.24 in

## Adjustability

Height adjustable

## Electric

System power: 30 W

## Protection

IP: 66