
## Product data sheet

LUCAS PIV (BOLLARD) 9.882.5521.35 LEIPZIGER LEUCHTEN



Decorative luminaire for lanes, driveways, terraces, gardens, and for night illumination and hazardous areas. - Impact-resistant clear/opal polycarbonate cylinder, UV-stabilized - Mirror lamellae for light guidance and glare limitation made of premium highest-grade aluminium, burnished and anodized - Unit carrier, crown flange and ornaments made of corrosion-resistant cast aluminium, painted; ground and passivated special steel parts preferably in jet black, RAL 9005 - Housing/upright tube of special steel painted in any RAL or DB colour without surcharge, or special steel, ground and passivated - All electrical components accommodated on a block -Crown detachable for easy maintenance/lamp change - Upright tube without pole door, incl. adapter jack Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711

## Light output 1



## 1 x Compact fluorescent lamp

IP 55

r x compact nucleocent lump			
Nominal lamp power	23 W	LOR	40%
Lamp flux	1500 lm	ULOR	21%
Luminous efficacy	26 lm/W	Total flux	597 lm
CCT	2571 K	Total power	23 W
CRI	90		

Electric
System power: 23 W
Protection
IP: 55

## Design

Color of housing: Black