

Product data sheet

LUCAS III (WALL FITTING BEADED)
9.837.3062.16
LEIPZIGER LEUCHTEN



Mounting heights between 4.00 - 6.00 m. - High-quality mirror optics to suit non-glare class KB1 - Aluminium cast luminaire body, inside white, outside painted in colour - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Luminaires with wiring ready for connection - Easy installation with adapter jack - Scope of supply includes complete unit with one/two painted special steel brackets - Available in any RAL or DB colour without surcharge Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

Light output 1



1 x High pressure mercury vapour lamp

Nominal lamp power	125 W	LOR	83%
Lamp flux	6800 lm	ULOR	2%
Luminous efficacy	41 lm/W	Total flux	5637 lm
CCT	3400 K	Total power	137 W
CRI	54		

Mounting mode

Wall mounted

Shape and measurements

Height: 22.44 in

Diameter: 22.44 in

Design

Material impression: Matt

Color of housing: White

Electric

System power: 137 W

Ballast: ECG

Suitable for feed-through wiring

Integrated sensors

Integrated sensors: Daylight sensor, Motion sensor

Protection

IP: 55

Designation labels: CE

Other operating numbers

Ambient temperature range: -4...95°F