Product data sheet

DIETER II (WALL FITTING) 9.839.2036.05

LEIPZIGER LEUCHTEN









Recommended mounting height 4.00 - 5.00 m. - Impact-resistant clear polycarbonate cylinder, UV-stabilized - Special steel frame, painted - Large aluminium reflector, underside finished in special white paint for max. light reflection - Mirror lamellae for light guidance and glare limitation made of premium highest grade aluminium, burnished and anodized - All electrical components on one block - Adapter jack connection - Lamps are easy to change -Available in any RAL or DB color without surcharge Voltage: 230V 50Hz Protected to: IP 65 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensated

Light output 1



1 x High pressure sodium vapour lamp				
Nominal lamp power	50 W	LOR		
Lamp flux	3500 lm	ULOR		
Luminous efficacy	29 lm/W	Total flux		
CCT	2000 K	Total power		
CRI	25			



i x High pressure sodium vapour lamp				
Nominal lamp power	70 W	LOR	52%	
Lamp flux	5600 lm	ULOR	13%	
Luminous efficacy	35 lm/W	Total flux	2898 lm	
CCT	2000 K	Total power	83 W	
CRI	25			

Mounting mode

Wall mounted

Shape and measurements

Height: 10.63 in Diameter: 10.63 in Electric

System power: 62-83 W

Protection

IP: 65

52% 13% 1811 lm 62 W