

# Product data sheet

GUSTAV II (1-ARMED)  
9.682.3062.07  
LEIPZIGER LEUCHTEN



IP  
55

Mounting height of 4.00 to 5.00 m for medium light requirements - Impact-resistant clear polycarbonate cylinder, UV-stabilized - Mirror lamellae for light guidance and glare limitation made of premium highest-grade aluminium, burnished and anodized - Aluminium reflector finished in special white paint for max. light reflection - Aluminium cover painted - Unit carrier made of corrosion-resistant cast aluminium, painted - All electrical components arranged on a block - Connection with adapter jack - Available in any RAL or DB colour without surcharge - Order pole, dia. 76 mm, separately Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensated

## Light output 1



### 1 x High pressure mercury vapour lamp

Nominal lamp power	125 W	LOR	54%
Lamp flux	6800 lm	ULOR	11%
Luminous efficacy	27 lm/W	Total flux	3648 lm
CCT	3400 K	Total power	137 W
CRI	54		

## Mounting mode

Pole top mounted

## Shape and measurements

Height: 29.13 in  
Diameter: 9.84 in

## Electric

System power: 137 W

## Protection

IP: 55