


Product data sheet

MICRO ORBITAL
03.3800/QR-CBC 51/50W/10°24°38°60°
FLOS




Family of embedded luminaires for halogen lamp direct network, 12V halogen and metal halide. Available in two sizes: Micro Orbital and Orbital. Available in finishes: white (30), black (14) and gray (02).

Light output 1




1 x Halogen low voltage lamp without reflector

Nominal lamp power	50 W	Socket	Gx5.3
Lamp flux	857 lm	LOR	100%
Luminous efficacy	17 lm/W	Total flux	857 lm
CCT	3000 K	Total power	50 W
CRI	99		




1 x Halogen low voltage lamp without reflector

Nominal lamp power	50 W	Socket	Gx5.3
Lamp flux	1054 lm	LOR	100%
Luminous efficacy	21 lm/W	Total flux	1054 lm
CCT	3000 K	Total power	50 W
CRI	99		



1 x Halogen low voltage lamp without reflector

Nominal lamp power	50 W	Socket	Gx5.3
Lamp flux	856 lm	LOR	100%
Luminous efficacy	17 lm/W	Total flux	857 lm
CCT	3000 K	Total power	50 W
CRI	99		



1 x Halogen low voltage lamp without reflector

Nominal lamp power	50 W	Socket	Gx5.3
Lamp flux	1182 lm	LOR	101%
Luminous efficacy	24 lm/W	Total flux	1189 lm
CCT	3000 K	Total power	50 W
CRI	99		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 3.54 in

Width: 3.54 in

Height: 4.72 in

Adjustability

Rotatable

Electric

System power: 50 W

Appliance Class: III

Protection

IP: 23