## Product data sheet

LUCAS VI (WALL FITTING BEADED) 9.832.3046.16

LEIPZIGER LEUCHTEN









High-quality mirror optics provide good glare protection and enable mounting heights between 4.00 - 6.00 m. - High-quality mirror optics to suit non-glare class KB1 - Aluminium cast luminaire body, inside white, outside painted in colour - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Scope of supply includes complete unit with one/two painted special steel brackets -Available in any RAL or DB colour without surcharge Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

## Light output 1



1 x High pressure mercury vapour lamp		
Nominal lamp power	50 W	
Lamp flux	2000 lm	
Luminous efficacy	28 lm/W	
CCT	3400 K	
CRI	54	

LOR	83%
ULOR	2%
Total flux	1658 ln
Total power	59 V



1 x High pressure mercury vapour lamp				
Nominal lamp power	80 W	LOR		
Lamp flux	4000 lm	ULOR		
Luminous efficacy	37 lm/W	Total flux		
CCT	3400 K	Total power		
CRI	54			

Electric

System power: 59-89 W

Shape and measurements Protection
Height: 22.44 in IP: 55

Diameter: 22.44 in

Mounting mode

Wall mounted

83% 2% 3316 lm 89 W