


Product data sheet

PURE 2 DOWNLIGHT
09.1714/QT-12/20W/35W/50W/75W/100W/21°
FLOS




Recessed luminaire for indoor application. For very low voltage halogen lamps or standard and discharge lamps. Self-extinguishing ceramic or engineering plastic lamp holders, with single-pole, transparent electric wires with double Teflon insulation.

Light output 1




1 x Halogen low voltage lamp without reflector

Nominal lamp power	100 W	Socket	Gy6.35
Lamp flux	2200 lm	LOR	81%
Luminous efficacy	18 lm/W	Total flux	1788 lm
CCT	3000 K	Total power	100 W
CRI	99		




1 x Halogen low voltage lamp without reflector

Nominal lamp power	75 W	Socket	Gy6.35
Lamp flux	1450 lm	LOR	81%
Luminous efficacy	16 lm/W	Total flux	1178 lm
CCT	2756 K	Total power	75 W
CRI	99		




1 x Halogen low voltage lamp without reflector

Nominal lamp power	50 W	Socket	Gy6.35
Lamp flux	910 lm	LOR	81%
Luminous efficacy	15 lm/W	Total flux	739 lm
CCT	3000 K	Total power	50 W
CRI	99		



1 x Halogen low voltage lamp without reflector

Nominal lamp power	35 W	Socket	Gy6.35
Lamp flux	600 lm	LOR	81%
Luminous efficacy	14 lm/W	Total flux	488 lm
CCT	3000 K	Total power	35 W
CRI	99		



1 x Halogen low voltage lamp without reflector

Nominal lamp power	20 W	Socket	E27
Lamp flux	300 lm	LOR	81%
Luminous efficacy	11 lm/W	Total flux	244 lm
CCT	2756 K	Total power	22 W
CRI	99		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 5.12 in

Width: 5.12 in

Height: 5.51 in

Adjustability

Rotatable, Tilttable

Electric

System power: 22-100 W

Appliance Class: I

Protection

IP: 20