


Product data sheet

PURE 3 SPOT TRACK
09.1916 /CDMR-111/70W/10°24°40°
FLOS




Luminaire for three-phase electric track installation. For very low voltage halogen lamps or standar and discharge lamps. Self-extinguishing ceramic or engineering plastic lamp holders, with single-pole, transparent electric wires with double teflon insulation.


Light output 1



1 x Metal halide lamp			
Nominal lamp power	70 W	Socket	Gx12
Lamp flux	6600 lm	LOR	57%
Luminous efficacy	54 lm/W	Total flux	3747 lm
CCT	2900 K	Total power	70 W
CRI	84		



1 x Metal halide lamp			
Nominal lamp power	70 W	Socket	Gx12
Lamp flux	6600 lm	LOR	45%
Luminous efficacy	42 lm/W	Total flux	2973 lm
CCT	2900 K	Total power	70 W
CRI	84		



1 x Metal halide lamp			
Nominal lamp power	70 W	Socket	Gx12
Lamp flux	6600 lm	LOR	30%
Luminous efficacy	28 lm/W	Total flux	1978 lm
CCT	2900 K	Total power	70 W
CRI	84		

Mounting mode

Ceiling mounted

Electric

System power: 70 W
Appliance Class: I

Shape and measurements

Length: 1.69 in

Width: 5.63 in

Height: 6.22 in

Adjustability

Free

Protection

IP: 20