Product data sheet


NADJA III (WALL FITTING) 9.846.3162.05 LEIPZIGER LEUCHTEN




IP 55

Recommended mounting height 3.50 - 5.00 m, other heights please inquire. - High-quality mirror optics guarantee excellent illumination and glare protection - All designs to suit non-glare class KB1 - Aluminium luminaire body, inside white, outside painted in colour - Aluminium unit carrier, painted white - Special reflector made of highest grade aluminium, burnished, anodized - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded -Available in any RAL or DB colour without surcharge Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

Light output 1



1 x High pressure mercury vapour lamp				
Nominal lamp power	125 W	LOR	78%	
Lamp flux	6800 lm	Total flux	5317 lm	
Luminous efficacy	39 lm/W	Total power	137 W	
CCT	3400 K			
CRI	54			



1 x High pressure mercury vapour lamp				
Nominal lamp power	80 W	LOR	78%	
Lamp flux	4000 lm	Total flux	3128 lm	
Luminous efficacy	35 lm/W	Total power	89 W	
CCT	3400 K			
CRI	54			

Mounting mode
Wall mounted
Shape and measurements

Height: 16.54 in Diameter: 16.54 in

Electric

System power: 89-137 W

Protection

IP: 55