


Product data sheet

GINEVRA
1110100 TC-TSE 33W
FLOS



• Outdoor/indoor floor lamp. • Configuration: vibrated and sandblasted concrete footing, extruded aluminium pole and white sanblasted polyethylene diffuser for a perfect light emission. • Double layer coating for high resistance to corrosion: The aluminium parts are painted with a double coat using powders which are complaint with QUALICOAT standards: a first layer of epoxy powder (with excellent chemical and mechanical resistance) and a second finishing layer of polyester powder (resistant to UV rays and atmospheric agents).The entire painting process of the aluminium fitting starts from components which have been sand-blasted in advance to make the surface more porous and increase the adherence of the paint. Ares effects alkaline and acid washing to clean the surfaces completely, then rinses with demineralised water to remove any residue particles, subsequently a chemical conversion treatment is done to protect against rusting.

Light output 1



1 x Compact fluorescent lamp

Nominal lamp power	33 W	Socket	E27
Lamp flux	2250 lm	LOR	98%
Luminous efficacy	67 lm/W	ULOR	53%
CCT	3000 K	Total flux	2200 lm
CRI	84	Total power	33 W

Mounting mode

Standing / Bollard, Floor mounted

Shape and measurements

Height: 23.62 in
Diameter: 19.69 in

Adjustability

Fixed

Electric

System power: 33 W
Appliance Class: I

Protection

IP: 65