

Product data sheet

EVA I
9.898.3046.00
LEIPZIGER LEUCHTEN



IP
55


For medium light requirements, mounting height 3.00 - 5.00 m. - Impact-resistant opal polyethylene attachment - Large aluminium reflector for max. light output, underside in special white paint - Unit carrier made of die cast aluminium, corrosion-resistant, outside painted in color - All electrical components are arranged on a block - Adapter jack for connection - Available in any RAL or DB colour without surcharge - Please order pole dia. 60 mm separately Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensated

Light output 1



1 x High pressure mercury vapour lamp

Nominal lamp power	50 W	LOR	82%
Lamp flux	2000 lm	ULOR	28%
Luminous efficacy	28 lm/W	Total flux	1633 lm
CCT	3400 K	Total power	59 W
CRI	54		



1 x High pressure mercury vapour lamp

Nominal lamp power	80 W	LOR	82%
Lamp flux	4000 lm	ULOR	28%
Luminous efficacy	37 lm/W	Total flux	3267 lm
CCT	3400 K	Total power	89 W
CRI	54		

Mounting mode

Pole top mounted

Shape and measurements

Height: 17.72 in
Diameter: 15.75 in

Electric

System power: 59-89 W

Protection

IP: 55