


Product data sheet

NORA I (WALL FITTING BEADED)
9.741.1032.06
LEIPZIGER LEUCHTEN



For medium light requirements, mounting height 3.50 - 4.00 m. - Impact-resistant clear or beaded polycarbonate attachment, UV-stabilized - Special reflector of premium highest-grade aluminium, burnished and anodized, for excellent illumination and glare protection -Aluminium luminaire body, inside finished in white paint, outside painted in colour - Aluminium unit carrier, painted white - Adapter jack connection - Available in any RAL or DB colour without surcharge - Scope of delivery includes special steel post/wall-mounted bracket, painted Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

Light output 1



1 x Metal halide lamp			
Nominal lamp power	70 W	LOR	73%
Lamp flux	7200 lm	ULOR	3%
Luminous efficacy	59 lm/W	Total flux	5269 lm
CCT	3000 K	Total power	89 W
CRI	90		

Mounting mode

Wall mounted, Ceiling mounted

Shape and measurements

Height: 21.26 in
Diameter: 21.26 in

Design

Material impression: Matt

Electric

System power: 89 W
Ballast: ECG

Protection

IP: 55
Designation labels: CE

Other operating numbers

Ambient temperature range: -13...113°F