


Product data sheet

VARIOPLAST I
672182.002.89
RZB




Series: VARIOPLAST I Luminaire for escape route illumination. Base: plastic (polycarbonate). Housing and diffusor: opal, made of shockproof plastic (polycarbonate). Driver integrated. For connection to the emergency power supply. With AC Control monitoring module for LUXIFAIR central battery units. Colour: white Length: 320 mm Width: 186 mm Height: 80 mm Weight: 0.95 kg Operating mode: maintained power mode Lamp: LED Socket: without socket Colour temperature: 4000K Colour rendering index (CRI): 80 System power: 7.7 W Rated luminous flux: 880 lm Luminous flux, emergency: 870 lm System power, emergency: 7.5 W Control gear: Regulated power supply Protection class: I Type of protection: IP 65

Light output 1 (integrated, emergency)



Lamp type	LED	CCT	4000 K
Nominal lamp power	7.5 W	CRI	80
Total flux	870 lm	LOR	100%
Luminous efficacy	116 lm/W	ULOR	6%
		Total power	7.5 W

Light output 2 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	7.7 W	CRI	80
Total flux	880 lm	LOR	100%
Luminous efficacy	114 lm/W	ULOR	6%
		Total power	7.7 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 7.32 in
Width: 12.60 in
Height: 3.15 in

Electric

System power: 15.2 W

Information regarding emergency functions

Supplementary emergency lighting
Emergency sign: N/A

Adjustability

Fixed

Protection

IP: 65

IK: 08