

# Product data sheet


RICHARD BI (FLOWER BED FITTING)  
9.880.3022.00  
LEIPZIGER LEUCHTEN



IP  
55

Decorative luminaire for lanes, driveways, terraces, gardens, and for night illumination and hazardous areas. - Impact-resistant clear/opal polycarbonate cylinder, UV-stabilized - Mirror lamellae for Richard BII made of burnished, anodized highest-grade aluminium - Reflector made of impact-resistant RESIST plexiglass, inside finished in white paint, outside painted in colour - Unit carrier made of corrosion-resistant cast aluminium, painted - Upright tube made of special steel, painted - Available in any RAL or DB colour without surcharge Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

## Light output 1



### 1 x High pressure mercury vapour lamp

Nominal lamp power	50 W	LOR	39%
Lamp flux	2000 lm	ULOR	13%
Luminous efficacy	13 lm/W	Total flux	783 lm
CCT	3400 K	Total power	59 W
CRI	54		

## Mounting mode

Standing / Bollard

## Shape and measurements

Height: 11.42 in  
Diameter: 7.09 in

## Electric

System power: 59 W

## Protection

IP: 55