

Product data sheet

LUCAS VIII (WALL FITTING)
9.828.3142.15
LEIPZIGER LEUCHTEN



IP
55


High-quality mirror optics provide good glare protection and enable mounting heights between 4.00 - 6.00 m. - High-quality mirror optics to suit non-glare class KB1 - Aluminium cast luminaire body, inside white, outside painted in colour - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Luminaires with wiring ready for connection - Easy installation with adapter jack - Scope of supply includes complete unit with one/two painted special steel brackets -Available in any RAL or DB colour without surcharge Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

Light output 1



1 x High pressure mercury vapour lamp

Nominal lamp power	50 W	LOR	80%
Lamp flux	2000 lm	ULOR	4%
Luminous efficacy	27 lm/W	Total flux	1593 lm
CCT	3400 K	Total power	59 W
CRI	54		



1 x High pressure mercury vapour lamp

Nominal lamp power	80 W	LOR	80%
Lamp flux	4000 lm	ULOR	4%
Luminous efficacy	36 lm/W	Total flux	3186 lm
CCT	3400 K	Total power	89 W
CRI	54		

Mounting mode

Wall mounted

Shape and measurements

Height: 22.44 in
Diameter: 22.44 in

Electric

System power: 59-89 W

Protection

IP: 55