

# Product data sheet

NADJA III (WALL FITTING BEADED)  
9.846.2036.06  
LEIPZIGER LEUCHTEN



Recommended mounting height 3.50 - 5.00 m, other heights please inquire. - High-quality mirror optics guarantee excellent illumination and glare protection - All designs to suit non-glare class KB1 - Aluminium luminaire body, inside white, outside painted in colour - Aluminium unit carrier, painted white - Special reflector made of highest grade aluminium, burnished, anodized - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Available in any RAL or DB colour without surcharge Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet


## Light output 1



### 1 x High pressure sodium vapour lamp

Nominal lamp power	50 W
Lamp flux	3500 lm
Luminous efficacy	44 lm/W
CCT	2000 K
CRI	25

LOR	78%
Total flux	2729 lm
Total power	62 W



### 1 x High pressure sodium vapour lamp

Nominal lamp power	70 W
Lamp flux	5600 lm
Luminous efficacy	53 lm/W
CCT	2000 K
CRI	25

LOR	78%
Total flux	4366 lm
Total power	83 W

## Mounting mode

Wall mounted

## Shape and measurements

Height: 16.54 in  
Diameter: 16.54 in

## Electric

System power: 62-83 W

## Protection

IP: 55  
Designation labels: CE, ENEC, F