## Product data sheet


LUCAS III (WALL FITTING) 9.837.2056.15 LEIPZIGER LEUCHTEN






Mounting heights between 4.00 - 6.00 m. - High-quality mirror optics to suit non-glare class KB1 - Aluminium cast luminaire body, inside white, outside painted in colour - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Luminaires with wiring ready for connection - Easy installation with adapter jack - Scope of supply includes complete unit with one/two painted special steel brackets - Available in any RAL or DB colour without surcharge Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

## Light output 1



1 x High pressure sodium vapou	rlamp	
Nominal lamp power	100 W	LOR

Norminal lamp power	100 VV	LUK	04%
Lamp flux	10400 lm	Total flux	8713 lm
Luminous efficacy	76 lm/W	Total power	115 W
CCT	2000 K		
CRI	25		



1 v High	pressure	eodium	vanour	lamn
т х піўн	pressure	soulum	vapour	iamp

0			
Nominal lamp power	70 W	LOR	84%
Lamp flux	5600 lm	Total flux	4691 lm
Luminous efficacy	57 lm/W	Total power	83 W
CCT	2000 K		
CRI	25		

Mounting mode	Electric
Wall mounted	System power: 83-115 W
Shape and measurements	Protection
Height: 22.44 in	IP: 55
Diameter: 22.44 in	

0/0/